

## DIN 963 - 4.8

## Cabeza plana ranura

Slotted countersunk head machine screw

Vis a metais tête fraisée fendue

Medida Size Dimension	Bicromatado Yellow Zinc Plated Bichromaté	Cincado Zinc plated Zingué	Cincado Negro Black Zinc plated Zingué Noir	Envasado Packing Emboitage	Embalaje Carton Emballage
mm.	€/1.000	€/1.000	€/1.000	Und.	Und.
M-3x6	16,40	16,40	24,60	500	9.000
M-3x8	16,40	16,40	24,60	500	9.000
M-3x10	16,95	16,95	25,45	500	9.000
M-3x12	18,25	18,25	27,40	500	9.000
M-3x15	19,50	19,50	29,25	500	9.000
M-3x20	24,50	24,50	36,75	500	9.000
M-3x25	28,90	28,90	43,35	500	4.500
M-3x30	32,75	32,75	49,15	500	4.500
M-3x35	45,30	45,30	67,95	200	3.600
M-3x40	50,30	50,30	75,45	200	3.600
M-4x8	29,55	29,55	44,35	500	9.000
M-4x10	25,80	25,80	38,70	500	4.500
M-4x12	26,45	26,45	39,70	500	4.500
M-4x15	28,90	28,90	43,35	500	4.500
M-4x20	32,05	32,05	48,10	500	4.500
M-4x25	48,45	48,45	72,70	500	3.000
M-4x30	50,95	50,95	76,45	500	3.000
M-4x35	52,80	52,80	79,20	200	1.800
M-4x40	59,05	59,05	88,60	200	1.800
M-4x45	74,90	74,90	112,35	200	1.800
M-4x50	87,40	87,40	131,10	200	1.800
M-4x60	98,15	98,15	147,25	200	1.200
M-5x8	34,55	34,55	51,85	200	3.600
M-5x10	32,75	32,75	49,15	200	3.600
M-5x12	36,45	36,45	54,70	200	3.600
M-5x15	40,25	40,25	60,40	200	3.600
M-5x20	46,55	46,55	69,85	200	1.800
M-5x25	57,90	57,90	86,85	200	1.800
M-5x30	59,80	59,80	89,70	200	1.800
M-5x35	71,75	71,75	107,65	200	1.800
M-5x40	79,25	79,25	118,90	200	1.800
M-5x45	100,00	100,00	150,00	200	1.200
M-5x50	114,50	114,50	171,75	200	1.200
M-5x60	135,25	135,25	202,90	100	900
M-6x10	54,15	54,15	81,25	200	3.600
M-6x12	48,45	48,45	72,70	200	1.800
M-6x15	57,90	57,90	86,85	200	1.800
M-6x20	67,95	67,95	101,95	200	1.800
M-6x25	78,00	78,00	117,00	200	1.800
M-6x30	87,40	87,40	131,10	200	1.200
M-6x35	101,25	101,25	151,90	200	1.200
M-6x40	108,25	108,25	162,40	200	1.200
M-6x45	127,75	127,75	191,65	100	600
M-6x50	137,15	137,15	205,75	100	600
M-6x60	152,80	152,80	229,20	100	600



800/1 TZ  
Ranura longitudinal  
Punta atornillador  
1/4" x 25

Ø Tornillo (mm.) ●

M-3	0,8x5,5
M-4	1,0x5,5
M-5	1,2x6,5
M-6	1,6x8,0

Especificaciones  
en pág. 148